

### Labtactics™ Countertop BOD Bottle Washer

Stop hand washing bottles and save time and money!

- Washes up to 16 BOD bottles per cycle
- Six programs to meet your cleaning needs
- Also washes other types of labware

**New**



Glassware washer 03660-40 shown with BOD bottle rack (BOD bottles not included)



Washer fits on cart for easy transport between washing areas.

Six programs of economy or sanitary modes, combined with the custom-designed spray arm, leaves BOD bottles sparkling clean. Sanitizing is accomplished by a 1200-watt heater that heats the water to 160°F (71°C). The unit comes with two racks—for BOD and general lab glassware—which are easily removed to transport or store the clean bottles. Use Alconox Detergent 8® detergent and Labtactics rinse agent listed below for best results. Washer has a white enameled steel exterior and 304 stainless steel interior; connects to any standard laboratory faucet.

**What's included:** fill and drain hoses with quick disconnects (5 ft), 5-gallon deionized water storage tank, BOD bottle rack, standard labware rack, 8 oz of rinse/dry agent, and 6-ft power cord.



#### Specifications

<b>Chamber dimensions:</b> 16½"W x 15½"H x 17½"D	<b>DI/distilled water supply</b> GPM: 0.8 gal./cycle psi: N/A gravity feed from 5-gallon reservoir
<b>Glassware clearance:</b> 10½"	<b>Drain line:</b> 5-ft hose to sink drain
<b>Washing temperature:</b> max 160°F (71°C)	<b>Power:</b> 115 VAC, 60 Hz; 1200 watts, 11.8 amps
<b>Hot water supply</b> GPM: 3.2 gal./cycle (max) psi: 20 to 90	<b>Exterior dimensions:</b> 22½"W x 19½"H x 17½"D

Catalog number	Washer type	Shpg wt lb (kg)	Price
R-03660-40	Countertop/cart mount	76 (34.5)	

R-03660-42 Rinse agent for Labtactics washer, 8 oz.....  
R-17775-10 Alconox Detergent 8. Case of 4 one-gallon bottles... /cs

**GO to page(s) 2347-2351**  
For additional glassware washers.

### StableTemp™ Undercounter BOD Incubator

Incubator holds up to 114 BOD bottles

- Microprocessor-based controller is conveniently mounted on the door for easy access
- Chamber interior features a two-amp outlet for auxiliary equipment



39063-00



Digital display shows temperature readings and active alarm.

Incubator includes a chamber safety thermostat set at 62°C. Digital LED display clearly shows temperature readings and alarm indicator. The LED alarm alerts you to over/under temperature conditions. Compressor is protected from accidental overload by a relay. Bottom rollers make installation, leveling, and moving simple.

**What's included:** chamber safety thermostat, 2 A outlet in the chamber, RTD temperature probe, compressor relay, shelves (two removable; three molded in door), and 8-ft power cord with U.S. standard plug.

#### Specifications

<b>Capacity:</b> 6.1 cu ft	<b>Resolution:</b> 0.1°C
<b>Temperature range:</b> -10 to 60°C	<b>Construction:</b> white plastic interior, white enameled steel exterior with foamed polyurethane insulation
<b>Accuracy:</b> ±0.2°C	<b>Dimensions (W x H x D)</b> Chamber: 21" x 28¼" x 20½" Overall: 24" x 34½" x 24½"
<b>Temperature uniformity:</b> ±1°C	
<b>Control type:</b> microprocessor	
<b>Display:</b> LED	

Catalog number	Power		Shpg wt lb (kg)	Price
	VAC, Hz	Amps		
ED-39063-00	115, 60	6	126 (57.0)	
ED-39063-05	230, 50	4		

115 VAC only **2 year warranty** Items over 100 lb

**GO to page(s) 962-963**  
For additional BOD incubators.